

MISE A JOUR DES VALEURS AERAULIQUES (Aa)
DES EXUPLUS POUR TETRAVOUTE
Exuplus

LA (mm)	LO (mm)	Rayon (mm)	corde		Av (m ²)	Aa (m ²)	PCA
			mini (mm)	maxi (mm)			
1460	2060	1750	1500	1900	3,01	1,93	10
			1700 (24V)				
		2350	1500	1899		1,84	16, 16PI
			1700 (24V)				
			1900	2999		1,93	10, 16 et 16PI
			3000	3600		1,96	
		4150	2500	3600		1,84	20, 20PI et 32
						1,96	16PI et 20PI
			3601	4000		1,96	10
				4500			
6000		1,96	16, 20 et 32				

2000	2060	2350	2000	2999	4,12	2,68	10, 16 et 16PI
			3000	3600		2,72	
		4150	2500	3600		2,51	20, 20PI et 32
			3601	4000		2,64	16PI et 20PI
				4500		2,64	10
				6000		2,64	16, 20 et 32

2000	3120	2350	2000	2999	6,24	4,12	10, 16 et 16PI
			3000	3600		4,18	
		4150	2500	3600		3,81	20 et 32
			3601	4000		4,06	16PI et 20PI
				4500		4,06	10
				6000		4,06	16, 20 et 32